

# JMB-E



These DiBO industrial stationary high pressure units have unlimited possibilities for different applications for professional and industrial use.

The **JMB-E** unit is equipped with a 70 kW DiBO GreenBoiler (18% Fuel saving) and is available in a version with a diesel engine electric starting (Model DE).

Due to its on-board power source and self-contained operation, the JMB-E hot water high-pressure cleaner is easy to use even in places where no electricity is available. It is ideally suited for a wide range of cleaning jobs, because it offers the choice of cold or hot water cleaning.

## EXCLUSIVE TECHNOLOGIES



Modern design



High quality materials



Robust frame



Radial high-pressure pump



Motor pump coupling using reduction gearbox



GreenBoiler



5 Year warranty



12h use

## PRODUCT SPECIFICATIONS

- A powder-lacquered steel frame → prevention from corrosion and robust
- High quality materials: UV-resistant and thick walled rotation casted polyethylene in combination with stainless steel → very solid, colourfast and scratch protection and no corrosion
- Easy to move by using a fork-lift truck
- 2 integrated lance holders → ergonomic
- Easy to use operation panel with ON/OFF switch and thermostat

## STANDARD EQUIPMENT

Code	Item description
1.208.520.020	High pressure hose (3/8", 10 m) → extended reach
1.211.525	High pressure gun with swivel → large manoeuvrability of the wash gun
1.216.729.xxxxx	Single stainless steel lance with high pressure nozzle and rotating quick coupling (≤ 250 bar)

## TECHNICAL SPECIFICATIONS

- High-tech heating system
  - 70 kW GreenBoiler for a greater efficiency > 92%
  - 18% fuel saving
  - Low CO2 emission
  - Low maintenance cost
- 12 V operating voltage for the electronic control unit and burner boiler
- Available as version with diesel engine, electrical starting (Model DE) and a 27 l fuel tank for motor and Greenboiler
- Radial high pressure pump with 3 ceramic plungers and stainless steel valves → fewer vibrations and less noise
- Engine/pump coupling via reduction gearbox
- Automatic air cooling
- Overheat protection for the motor
- Coarse particle filter
- Pressure gauge
- Vibration damper
- Automatic idling → less consumption (\*)
- Pressure relief up to <25 bar with sealed gun → safety

## MODELS

Code	Description	bar	l/h	°C	kW	kW	l	m	mm	kg	
1.126.340	JMB-E 200/15 DE	200	180 - 900	30 - 125	7,5 (diesel)	70	27	10	1166 x 642 x 1120	322	045

## OPTIONAL EQUIPMENT

Code	Item description
1.226.020	Supplement for hose reel with 20 m high pressure hose for JMB-E



## OPTIONAL ACCESSORIES

Code	Item description
1.226.025	Hose reel set with 20 m high pressure hose for JMB-E

